


F16.1







FIG.4

(a)		(b)
SEQUENCE No.		IP HEADER
RTP HEADER		UDP HEADER
		RTP HEADER
APPLICATION DATA		
	9	MPEG DATA







FIG.7



TYPE OF CONTENT	TYPE OF JUDGING PARAMETER	MONITORED VALUE (X)	MULTIPLIER
Α	PACKET ARRIVAL RATE	90%≤X	1
	٠.	70≦X<90%	8.0
		50≤X<70%	0.5
		X<50%	0
В	PACKET ARRIVAL RATE WITHIN ALLOWABLE FLUCTUATION TIME	90%≦X	1
		70≦X<90%	0.7
		X < 70%	0
•			·
•		b	
	·		





FIG.9



TYPE OF CONTENT	TYPE OF JUDGING PARAMETER	MONITORED VALUE(X)	MULTIPLIER
Δ	PACKET ARRIVAL RATE	90%≤X	1
		70≦X<90%	0.8
·		50≦X<70%	0.5
		X < 50%	0
В	B PACKET ARRIVAL RATE WITHIN ALLOWABLE FLUCTUATION TIME	90% ≤X	1
		70≦X<90%	0.7
		X < 70%	0
	·		
·	. ý.		
٠٠.		٠ .	
•			






FIG.11





F16.12